

### AFTER APPLICATION

- 1 DO NOT** handwash your vehicle for 3 days to allow time for the adhesive to cure.
- 2 DO NOT** machine or spray wash your vehicle for 7 days after application.
- 3 DO NOT** run your vehicle through an automated wash for 14 days after application.
- 4 DO NOT** wax with traditional car wax. Only use 247 Graphx approved Wrap Polish.
- 5 DO** follow the cleaning instructions below, excerpted from 3M Technical Bulletins. Failure to follow them will void your warranty.

### WASHING THE GRAPHICS

- 1 Use a cleaner which is non-abrasive, neither strongly acidic or alkaline, and is free of alcohol or solvents. Wrap wash is available through 247 Graphx Studios Inc.
- 2 Flush the graphic's surface with clean water to remove loose dirt particles.
- 3 Wash the marking with a rag or sponge using a detergent which complies with Step 1. Avoid abrading the surface by unnecessary scrubbing. Once suds have been applied, rinse with a steady stream of water.
- 4 If using a pressure washer, the nozzle must be at least twelve inches away from and perpendicular to the marking. Pressure must not exceed 1500 psi and water temp must not exceed 180°F. Do not direct the water stream at the edge of the marking or edge-lifting will occur.
- 5 Use of automatic car washes with rotating brushes is not advised unless the brushes are cloth. Only Boomerang Automated Car Wash is approved by 247 Graphx Studios Inc. with no more than one wash every 15 days.  
**NYLON BRUSHES WILL DAMAGE THE GRAPHICS**
- 6 If tar, oil, diesel smut or bituminous material remains, wipe with a rag dampened with kerosene, mineral spirits, heptane or VM&P Naphtha. Do not use other solvents. Wash again with detergent and water. Rinse with clean water.

BUSINESS:

DATE WRAPPED:

YEAR:

MAKE:

MODEL:

STAGE 1

STAGE 2

STAGE 3

HD WRAP



If you have any additional questions about maintenance, please contact us. Thank you for your business.

P: 405.677.7775

F: 405.601.9289

[WWW.247GSI.COM](http://WWW.247GSI.COM)